


# It's a Lantech!

## Work smarter... Keep your driver on the forklift!

- All of the features and benefits of our popular Q-300 with automation added:
  - (1) Patented XT Cut and Clamp® automatically captures the stretch film and cuts it at the end of the wrap cycle.
  - (2) Save two minutes of forklift driver labor per load.
- No scheduled preventative maintenance.





Q-300XT  
\*Shown with Click-n-Go  
Remote Control option.

# Q-300XT

Eliminate the "run-around" with Simple Automation™ in a fast - paced environment.

Q-300XT automatically attaches and cuts the film. Equipped with a fully protected mechanical cut & clamp. Improve productivity by keeping the operator on the forklift.



## Q-300XT Specifications

### PERFORMANCE CRITERIA

■ Production Speed	30-40 loads per hour
■ Maximum Load Diagonal	175 cm Recommended
■ Maximum Load Height	203 cm
■ Maximum Load Weight	1800 kg

### LOAD HANDLING SYSTEM

■ Turntable Drive	1 HP TEFC Motor
■ Turntable Speed	1-12 RPM
■ Turntable, Smooth Top	165 cm

### FILM DELIVERY SYSTEM

■ Power-Roller Stretch Plus System	200% Standard (100%-300% available)
■ Wrap Force	Electronically controlled
■ Film Capacity	25.4 cm Roll Dia., 50.8 cm Film Web

### MACHINE SHIPPING WEIGHT

■ Machine size	170 cm W x 305 cm L x 236 cm H
■ Shipping Weight (including skid - approximate)	748 kg. (excludes ramp)

### ELECTRICAL REQUIREMENTS

■ Machine Voltage	240V, 16 Amp
■ Microcontroller	Standard
■ Wrap Cycle Pause	Standard

### SERVICE SUPPORT PHONE NUMBER

24 hrs/7 days a week  
800-866-0322

Specifications subject to change without notice. Lantech systems and sub-systems are protected by U.S. and foreign patents. Additional U.S. and foreign patents pending. © Lantech

## Boost your machine's performance with these features:

### Pallet Grip®

Don't Take More Risk Than You Have To!

Millions of loads slide off their pallets during shipment each year, causing billions of dollars of rework and waste.

Pallet Grip (patented) rolls up a film cable and drives it down onto the pallet, locking the load. This makes sure your load does not slide off during transit.




### EZ Weigh™ Integrated Scale

Check Every Load for Quality and Freight Cost!

Weigh and wrap in one easy step.

Patented built-in weigh system is fully integrated into the turntable. Same footprint as standard Q semi-automatic.



### Click-n-Go™

Stretch Wrapping Loads at the Touch of a Button!

Enhances portability by eliminating requirement to install a ceiling-mounted lanyard.

Each unit can handle up to 3 machines.

Click-n-Go remote meets the latest safety requirements outlined by the National Electrical Code. Using infrared technology and two-step activation process, the Click-n-Go is immune to accidental activation from stray radio frequency.

